

STANDARD SUPPLY RANGE

TYP	Pressure rating [psi]	2K	3K	5K	10K	Drift- Ø [mm]	Hartmann ball valve overall length [mm]	Comparison with standard overall length as per API 6A [mm]		Ring nut	Article number	Adaption		Drainage [inch]	
								Nominal bore [inch]	Ball valve			Gate Valve	F12		SW
ASF	1 - 13/16 x 1 (reduced)				●	25,4	464	-	-	BX151	55000043	-	SW15	-	
											55000044	F12	Ø30		
	1 - 13/16				●	46	464	464	464	BX151	10078264	-	SW32		
											10082605	F16	Ø60		
AST	2 - 1/16	●				52,5	295	295	295	R23	10078300	-	SW19		
			●	●			371	371	371	R24	10078302	-	SW27		
					●		521	521	521	BX125	10082601	F14	Ø40		
													10082600		F16
	3 - 1/8	●				79,5	359	359	359	R31	10078235	-	SW27	½ NPT	
			●				384	384	435	R31	10078230	-	SW27		
				●			473	473	473	R35	10078205	-	SW27		
	3 - 1/16				●	78	619	619	619	BX154	10078203	F25	Ø60		
		●					435	435	435	R37	10078192	F16	Ø40		
			●				460	460	511	R37	10078099	F16	Ø40		
				●			549*	549	549	R39	10080584	F16	Ø60		
					●		683**	549	549	R39	10078095	F16	Ø60		
							670	670	670	BX155	10076954	F25	Ø70		
	5 - 1/8	●				130,2	562	-	562	R41	10078146	F16	Ø50		
			●				613	-	613	R41	10076956	F16	Ø50		
				●			727	-	727	R44	10078090	F25	Ø60		
	7 - 1/16 x 6 - 3/8 (reduced)	●				162,1	613	-	-	R45	10078103	F25	Ø70	¾ NPT	
			●				613	-	-	R45	10078092	F25	Ø70		
				●			737	-	737	R46	10078089	F25	Ø70		
	7 - 1/16	●				179,4	664	-	664	R45	10078074	F25	Ø60		
		●			714		-	714	R45	10078076	F25	Ø60			
			●		813		-	813	R46	10080585	F25	Ø80			
				●	840**		-	813	R46	10078088	F25	Ø80			
9	●				228,6	787	-	-	R49	10078118	F30	Ø100			
		●				787	-	-	R49	10076916	F30	Ø100			
			●			972**	-	1041	R50	10076934	F30	Ø100			
				●		1041	-	1041	R50	10077098	F30	Ø100			
11 x 10 (reduced)	●				254	841	-	-	R53	10078133	F30	Ø100	1 NPT		
		●				841	-	-	R53	10078087	F30	Ø100			
			●			1092	-	-	R54	10078067	F35	Ø100			

* Housing side with block flange (studded design)

** Customs dimensions– can also be supplied on request

LEAD TIME: 12 weeks. Shorter delivery upon request