

STANDARD LIEFERPROGRAMM

TYP	Druckstufe [psi]	2K	3K	5K	10K	Drift-Ø [mm]	Baulänge Hartmann Kugelhahn [mm]	Vergleich Normbaulängen gemäß API 6A [mm]		Ringnut	Artikelnummer	Adaption		Entwässerung [inch]			
								Nennweite [inch]	Kugelhahn			Gate Valve	-		-	SW15	Ø30
ASF	1 - 13/16 x 1 (reduced)				●	25,4	464	-	-	BX151	55000043	-	SW15				
											55000044	F12	Ø30				
	1 - 13/16				●	46	464	464	464	BX151	10078264	-	SW32				
											10082605	F16	Ø60				
AST	2 - 1/16	●					295	295	295	R23	10078300	-	SW19				
											10082603	F12	Ø25				
			●	●			52,5	371	371	371	R24	10078302	-	SW27			
						●						10082601	F14	Ø40			
							521	521	521	BX125	10082600	F16	Ø40				
	3 - 1/8	●						359	359	359	R31	10078235	-	SW27			
												10082599	F12	Ø30			
			●				79,5	384	384	435	R31	10078230	-	SW27			
						●		473	473	473	R35	10078205	-	SW27			
											10082597	F14	Ø40	½ NPT			
	3 - 1/16				●	78	619	619	619	BX154	10078203	F25	Ø60				
	4 - 1/16	●						435	435	435	R37	10078192	F16	Ø40			
			●					460	460	511	R37	10078099	F16	Ø40			
					●		103,2	549*	549	549	R39	10080584	F16	Ø60			
					●			683**	549	549	R39	10078095	F16	Ø60			
						●		670	670	670	BX155	10076954	F25	Ø70			
	5 - 1/8	●						562	-	562	R41	10078146	F16	Ø50			
			●				130,2	613	-	613	R41	10076956	F16	Ø50			
					●			727	-	727	R44	10078090	F25	Ø60			
	7 - 1/16 x 6 - 3/8 (reduced)	●						613	-	-	R45	10078103	F25	Ø70			
			●			162,1	613	-	-	R45	10078092	F25	Ø70				
				●			737	-	737	R46	10078089	F25	Ø70	¾ NPT			
7 - 1/16	●						664	-	664	R45	10078074	F25	Ø60				
		●				179,4	714	-	714	R45	10078076	F25	Ø60				
				●			813	-	813	R46	10080585	F25	Ø80				
				●			840**	-	813	R46	10078088	F25	Ø80				
9	●						787	-	-	R49	10078118	F30	Ø100				
			●			228,6	787	-	-	R49	10076916	F30	Ø100				
				●			972**	-	1041	R50	10076934	F30	Ø100				
				●			1041	-	1041	R50	10077098	F30	Ø100	1 NPT			
11 x 10 (reduced)	●						841	-	-	R53	10078133	F30	Ø100				
		●				254	841	-	-	R53	10078087	F30	Ø100				
				●			1092	-	-	R54	10078067	F35	Ø100				

* gehäuseseitig mit Blockflansch (studded design)

** bereits gelieferte Sonderbaulänge - ebenfalls auf Anfrage lieferbar

LIEFERZEIT: 12 Wochen. Kürzere Lieferzeiten gegen Aufpreis möglich.